

Beny 2 Guns Wall-mounted DC EV Charger

40kW / 60kW



Datasheet

Zhejiang Benyi New Energy Co.,Ltd.

Shuanghuanglou Industrial Zone, Beibaixiang Yueqing,zhejiang P.R. China

TEL: +86-577-5717 7008 FAX: +86-577-5717 7007

✉ info@evb.com 🏠 Importer:xxxxxxx

🌐 www.evb.com 📍 Address:xxxxxxx

♻️ This catalogue has been printed on ecological paper .

© Zhejiang Benyi New Energy Co., Ltd. All rights reserved.

⚠️ If the models and specifications in this product catalogue change due to product updates, we will not provide prior notification.



VERSION: 20250304-01

WWW.EVB.COM

Product Overview

The Beny 2 Guns Wall-mounted DC EV Charger is equipped with an impressive 7-inch touch screen that offers intuitive control. Rest assured that we have certifications such as CE and RCM, as well as comprehensive full protection features. Enjoy convenient app control and Ethernet/4G/WiFi connection, and charge your EV confidently and efficiently!



Product Advantages



7-inch touch screen



IP55 Rating



Ethernet/4G/WiFi



RFID



APP Control



Full Protection



OCPP 1.6J

WWW.EVB.COM



Model Selection

Wall-mounted DC EV Charger		BBDC40-D	BBDC60-D
			
Structure Description			
Shell Material		Galvanized Sheet	
Dimension		705*735*330(L*W*H mm)	
Packing Dimension		1010*905*795(L*W*H mm)	
Weight		≤140kG	≤150kG
Installation Method		Wall-mounted	
Cable Routing		Bottom Inlet Wiring,Bottom Outlet Wiring	
Total length of gun cable		5 m	
Charging Outlets	Double(CCS1+CCS1)	Double (CCS2+CHADEMO)	Double (CCS1+NACS)
	Double (CCS1+CHADEMO)	Double(CHADEMO+GBT)	Double(CCS2+NACS)
	Double(CCS2+GBT)	Double(CCS1+CCS2)	Double(GBT+NACS)
	Double(CHADEMO+CHADEMO)	Double(CCS1+GBT)	Double(CHADEMO+NACS)
	Double(CCS2+CCS2)	Double(GBT+GBT)	Double(NACS+NACS)
Connectivity Authorization		RFID, App	
Screen		7 Inch LCD Screen/LED Light	
Electrical Specification			
AC Input Voltage		AC380V-415V, 3P+N+PE	
Rated Input Current		68A	102A
Input Frequency		50Hz/60Hz	
Consumption		≤20W	
Rated Power		40kW	60kW
Output Voltage Range		CCS1/CCS2/GBT/NACS: 150Vdc –1000Vdc;CHADEMO: 150Vdc –500Vdc	
Output Current		CCS1/CCS2:0~133.3A; GBT/NACS:0~133.3A; CHADEMO:0~125A	CCS1/CCS2:0~200A; GBT/NACS:0~200A; CHADEMO:0~125A
Efficiency		≥95%	
Power Factor		≥0.99(load:100%)	

Functionate Design	
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4:2019, EN IEC 61851-21-2: 2021
communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30℃~+85℃
Working Temperature	-30℃~+50℃
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightening Surge Protection